

VERSACOOLER RANGE

Surface-Mounted Bubblers

Models: AC-PV8ACY Manual Dispense, Refrigerated, Vandal-Resistant
AC-PVAC Manual Dispense, Non-Refrigerated, Vandal-Resistant

VersaCooler AC-PV8ACY

Delivering 60LPH of 10°C water at 21°C ambient.
Cooling system uses R-134a refrigerant.

VersaCooler AC-PVAC

Delivering ambient drinking water.

These surface mount drinking fountains are manually activated via the vandal-resistant touch-button.

Key VersaCooler moulded components shall contain Freshield, which utilises a silver-based antimicrobial compound that reduces the growth of micro-organisms and mildew to protect the surfaces from discolouration, odours and degradation.

Complies with ANSI A117.1 and ADA. Shall comply with all relevant VE directives (LVD, EMC, RoHS). Shall comply with ANSI/NSF 61.

Suitable for public building, gymnasiums, sports complexes, hospitals, schools, and offices.



Model Code	AC-PV8ACY	AC-PVAC
Activation	Mechanical (Vandal-Resistant touch-button)	
Filtration	Filter (optional), Built-in 100 micron strainer	
Disinfection	Ultra Blu V (optional)	
Auto-Off Water Flow	No	
Water Connections	Inlet: 1/2" BSP connector, Drain: 40mm Female Socket (Not trapped)	
Exterior	Antimicrobial ABS Plastic, Brushed Stainless Steel	
Chassis	Heavy Duty Galvanised Steel	
Dimensions	480(H) x 448(W) x 473(D)	
Net Weight	27 kg	11 kg
Power Supply	220-240V, 50/60 Hz	-
Cooling Performance	60 LPH Rated Capacity & Base Rate (10°C in 21°C amb. temp.)	Non-Refrigerated
Full Load Amps	2.2A	-
Rated Watts	450 W	-
Energy System	Refrigeration is on only when in use or if water temp increases during long period of standby.	-
Country of Origin	Mexico	
Certifications	WaterMark, ANSI/NSF 61, CABO/ANSI A117.1, ADA, CE (LVD, EMC, RoHS)	
Warranty	1 Year Full, 2 Years Parts Only	

Your Partner in Cool.

AQUA
COOLER

TECHNICAL DRAWINGS

