

# VERSAFILLER RANGE

Surface Mounted All-In-One

Models: AC-PV8SBFSLY Manual Dispense, Refrigerated, Split-Level, Vandal-Resistant

## Versafiller AC-PV8SBFSLY

Delivering 60LPH of 10°C water at 21°C ambient.  
Cooling system uses R-134a refrigerant.

These surface mount hydration station combos are manually activated. The bottle filler requires a push of the touch-button, while the drinking fountains are activated via the vandal-resistant touch-buttons.

Key Versafiller moulded components shall contain Freshield, which utilises a silver-based antimicrobial compound that reduces the growth of micro-organisms and mildew to protect the surfaces from discolouration, odours and degradation.

Suitable for public building, gymnasiums, sports complexes, hospitals, schools, and offices.



Model Code	AC-PV8SBFSLY
<b>Activation</b>	Bottle Filler: Manual (Touch-button) Drinking Fountain: Manual (Vandal-Resistant Touch-button)
<b>Sensor Coverage</b>	Up to 5cm (approx.)
<b>Filtration</b>	Filter (optional), Built-in 100 micron strainer
<b>Auto-Off Water Flow</b>	Bottle Filler: Yes ; Drinking Fountain: No
<b>Water Connections</b>	Inlet: 1/2" BSP connector, Drain: 40mm Female Socket (Not trapped)
<b>Exterior</b>	Antimicrobial ABS Plastic, Brushed Stainless Steel
<b>Chassis</b>	Heavy Duty Galvanised Steel
<b>Dimensions</b>	960(H) x 895(W) x 473(D)
<b>Alcove Height</b>	250 mm
<b>Net Weight</b>	31 kg
<b>Power Supply</b>	220-240V, 50/60 Hz
<b>Cooling Performance</b>	60 LPH Rated Capacity & Base Rate (10°C in 21°C amb. temp.)
<b>Full Load Amps</b>	2.2A
<b>Rated Watts</b>	450 W
<b>Energy System</b>	Refrigeration is on only when in use or if water temp increases during long period of standby.
<b>Country of Origin</b>	Mexico
<b>Certifications</b>	WaterMark, ANSI/NSF 61, CABO/ANSI A117.1, ADA, CE (LVD, EMC, RoHS), WRAS
<b>Warranty</b>	1 Year Full, 2 Years Parts Only

Your Partner in Cool.

**AQUA  
COOLER**

