

# VERSAFILLER RANGE

## Surface Mounted All-In-One

Models: AC-PV8SBFY Manual Dispense, Refrigerated, Vandal-Resistant  
AC-PVSBF Manual Dispense, Non-Refrigerated, Vandal-Resistant

### Versafiller AC-PV8SBFY

Delivering 60LPH of 10°C water at 21°C ambient.  
Cooling system uses R-134a refrigerant.

### Versafiller AC-PVSBF

Delivering ambient drinking water.

These surface mount hydration station combos are manually activated. The bottle filler requires a push of the touch-button, while the drinking fountain is activated via one of four push-pads.

Key Versafiller moulded components shall contain Freshield, which utilises a silver-based antimicrobial compound that reduces the growth of micro-organisms and mildew to protect the surfaces from discolouration, odours and degradation.

Suitable for public building, gymnasiums, sports complexes, hospitals, schools, and offices.



Model Code	AC-P8SBFY	AC-PSBF
<b>Activation</b>	Bottle Filler: Manual (Touch-Button) Drinking Fountain: Manual (Vandal-Resistant Touch-button)	
<b>Filtration</b>	Filter (optional), Built-in 100 micron strainer	
<b>Auto-Off Water Flow</b>	No	
<b>Water Connections</b>	Inlet: 1/2" BSP connector, Drain: 40mm Female Socket (Not trapped)	
<b>Exterior</b>	Antimicrobial ABS Plastic, Brushed Stainless Steel	
<b>Chassis</b>	Heavy Duty Galvanised Steel	
<b>Dimensions</b>	960(H) x 413(W) x 473(D)	
<b>Alcove Height</b>	250 mm	
<b>Net Weight</b>	31 kg	16 kg
<b>Power Supply</b>	220-240V, 50/60 Hz	-
<b>Cooling Performance</b>	60 LPH Rated Capacity & Base Rate (10°C in 21°C amb. temp.)	Non-Refrigerated
<b>Full Load Amps</b>	2.2A	-
<b>Rated Watts</b>	450 W	-
<b>Energy System</b>	Refrigeration is on only when in use or if water temp increases during long period of standby.	-
<b>Country of Origin</b>	Mexico	
<b>Certifications</b>	WaterMark, ANSI/NSF 61, CABO/ANSI A117.1, ADA, CE (LVD, EMC, RoHS), WRAS	
<b>Warranty</b>	1 Year Full, 2 Years Parts Only	

Your Partner in Cool.

**AQUA**  
**COOLER**

# TECHNICAL DRAWINGS

