

FREE STANDING BOTTLE FILLER

Free standing, mains-connected, bottle filler units

The Free Standing Bottle Filling Station is perfect for those high traffic areas. With a contactless, touch-free activation - there are no fears of crosscontamination.



KEY FEATURES

- Against-a-wall bottle filler
- Contactless (touch free) activation with shut off timer
- Built-in bottle counter, filter monitor and programmable timeout feature
- Large alcove to fit most sports bottles
- Energy-efficient LEDs illuminate alcove and aids bottle filling
- Built-in drain - no drip tray to empty
- Built-in 100 micron strainer stops particles before they enter the waterway
- Waterways are lead-free in materials & construction
- Heavy duty steel frame
- Refrigerated, delivers chilled and ambient water
- Standard cabinet finish: white powder coated atainless steel

These free standing bottle fillers include an electronic sensor for a contactless (touch free) activation and a 30 second shut off timer.

Moulded components contain Freshield, which utilises a silverbased antimicrobial compound that reduces the growth of microorganisms and mildew to protect the surfaces from discolouration, odours and degradation.

Complies with ANSI A117.1 and ADA. Shall comply with all relevant CE directives (LVD , EMC, RoHS). Shall comply with ANSI/NSF 61.

Suitable for public building, gymnasiums, sports complexes, hospitals, schools, and offices. The sloped top prevents rubbish being placed on the unit. The unit can be installed right against the wall to save space.



Model Information (AC-P8FSZEBFY)

Activation	Contactless (Infrared Sensor)
Sensor Coverage	Up to 5cm (approx.)
Filtration	Filter (optional), Built-in 100 micron strainer
Water Connections	Inlet: 1/2" BSP connector, Drain: 40mm Female Socket (Not trapped)
Exterior	Standard White.
Chassis	Heavy Duty Galvanised Steel
Dimensions	1525(H) x 600(W) x 300(D)
Alcove Height	265mm
Net Weight	55kg
Power Supply	220-240V, 50/60 Hz
Cooling Performance	30 LPH - Rated Capacity & Base Rate - (10°C in 21°C amb. temp.)
Full Load Amps	4.8 A
Rated Watts	550 W
Country of Origin	Poland
Certifications	WaterMark, CE (LVD, EMC, RoHS)
Warranty	1 Year Full, 2 Years Parts Only

Your Partner in Cool.

**AQUA
COOLER**

TECHNICAL DRAWINGS

AC-P8FSZEBFY

