

# MK SERIES

Premium, Heavy-Duty, Free-Standing Drinking Fountain

Designed for high usage, demanding environments.



## KEY FEATURES

- 35L/h cold water output
- Extra large, 8L capacity Industrial grade 304 stainless steel tank
- Polished stainless steel top
- Auto return heavy duty glass filler tap
- Choice of grey powdercoast or stainless steel cabinet
- Adjustable, tamper proof non-squirt bubbler with soft touch protection
- 2 year warranty
- Australian watermark compliant

Designed for high-usage environments, the MK Series is a premium, heavy-duty free-standing drinking fountain, ideal for gyms, schools, workplaces, public spaces, sports facilities, and public areas. Engineered for durability and performance, it delivers a reliable supply of chilled water, even in the most demanding conditions.

With a cooling capacity of 35 litres per hour and an extra-large 8-litre storage tank, the MK Series ensures a steady flow of cold water, making it perfect for busy areas. The heavy-duty, auto-return tap is built for longevity, while the soft-finish bubbler provides a comfortable and hygienic drinking experience. Available in either a grey powder coat or stainless steel finish, this unit seamlessly integrates into a variety of environments. Fully WaterMark compliant and backed by a two-year warranty, the MK Series offers peace of mind with its robust construction and industry-leading reliability.

Ideal for locations that demand high performance and durability, the MK Series drinking fountain is a trusted choice for ensuring access to fresh, chilled water in busy settings.



Stainless Steel



Grey Powder Coat

## Model Selection Chart

Cooling Capacity: 35 Litres Per Hour with 8L Storage Tank		
86 servings of 500ml water per hour		
Bubbler & Glass Filler		
Cabinet	Filtered	
Grey Powder Coat	No	AC-MK11
	Yes	AC-MK11F
Stainless Steel	No	AC-MK11SS
	Yes	AC-MK11FSS

# TECHNICAL SPECIFICATIONS

Water Reservoir	8L water tank is fabricated from industrial grade 304 stainless steel for longevity.
Cooling Capacity	35 Lph (≤ 10c )
Refrigeration	Uses R134A refrigerant which is non-toxic, non-flammable and environmentally sympathetic. The refrigerant flow is controlled by a capillary tube, which has no moving parts.
Water Flow Controls	The bubbler is rated to supply 1.7 L/m at mains water pressure of between 140 and 700 kPa.
Water Inlet	1/2" Male B.S.P.
Water Outlet	40mm Female P.V.C. Socket
Thermostat Control	The thermostat is factory set
Condenser	Copper tube and expanded aluminium fin
Electrical	Consumption: 232 W 220-240 V, 50/60 Hz
IP Rating	IP33 Designed
Dimensions (Packed)	330(W) x 330(D) x 1150(H)
Warranty	Twelve month comprehensive coverage, additional twenty-four month compressor replacement.

