

# SU650 SERIES

## Outdoor Drinking Fountain and Bottle Refill Station

The SU650 is a strong and robust fountain perfect for schools and outdoor areas. Australian-made and fully WaterMark approved, the range can house an additional bottle filler with integrated catchment tray for on-the-go refills. The range is available in two standard colours or you have the option to retain the body's industrial galvanised finish.



### KEY FEATURES

- External bottle filler and catchment tray
- Vandal resistant 316 stainless steel security screws
- Stainless steel basin
- Available in hot dipped galvanised or powder coating (2 colours)

Sturdy and resilient while dispensing pure water, Aqua Cooler's new SU650 water fountains are at home anywhere in the outdoors. With a secondary water bottle refill fountain as well as the standard fountain feature, the SU650 provides on-the-go hydration whether you're in the schoolyard, the park, or even just between meetings in an office complex.



### Technical Specifications

|                   |                                                                                                                |               |
|-------------------|----------------------------------------------------------------------------------------------------------------|---------------|
| Water Connections | Water Inlet                                                                                                    | ½" Male B.S.P |
|                   | Drain                                                                                                          | 40mm          |
| Warranty          | 2 year manufacturers guarantee against faulty materials and workmanship under normal wear and tear conditions. |               |

|              |           |
|--------------|-----------|
| Total Height | 1000mm    |
| Diameter     | 275mm     |
| Body         | 5mm steel |

Your Partner in Cool.

**AQUA  
COOLER**

# TECHNICAL DRAWINGS

## GENERAL NOTES

ALL DIMENSIONS IN MILLIMETRES.

ENSURE FOUNTAIN IS CLEAN OF CONCRETE SLURRY OR SPRAY WHEN INSTALLED TO PREVENT STAINING OR DAMAGE TO APPLIED FINISHES.

PRE-FLUSH WATER LINE OF ALL DEBRIS BEFORE CONNECTING TO FOUNTAIN.

FOUNTAIN IS TO BE MOUNTED VERTICAL.

ALL CONCRETE TO BE GRADE N25 BROOM FINISHED 125mm MIN THICKNESS. ALL CONCRETE WORKS TO BE REINFORCED MIN SL72 MESH.

ALL INFORMATION & DRAWINGS ARE INDICATIVE ONLY.

